



PRODUCT FEATURES

LIVE STREAMING VIDEO AND SECURITY CAMERA

SAPPHIRE PAN-TILT-ZOOM SERIES

Secure and stream the jobsite 24/7 with the Sapphire PTZ video camera and security monitoring functionality. With the power to closely zoom in, detect motion and remotely-control your views, it's easy to look out for risks and monitor progress from anywhere. Sapphire offers a 360° field of view, panoramic images and UHD 4K optical zoom for clear visibility.





Get smart security features and real-time alerts

Motion detection is automatically included in every Sapphire camera, and focuses on true threats — filtering out bugs, birds and distant traffic.

- AI based object detection and classification
- Customizable monitoring hours
- Instant alerts help you self-manage security

Add a first line of defense to the jobsite

Save time and resources by directing motion alerts to professional monitoring agents. They'll review and dispatch police as needed.

- UL-Certified
- 5 Diamond
- TMA Member



Deter threats with optional hardware

Add lights, alarms and talk down speakers to your camera to combat theft and trespassing. Optional hardware helps support common Builder's Risk Insurance requirements and are solar-compatible.

- Blue strobe light and siren
- Talk down speakers
- Anti-tamper switch
- Onboard battery backup



SAPPHIRE SERIES
VIDEO PTZ SPECIFICATIONS

| | 8 Megapixel (3840 x 2160) | 2 Megapixel (1920 x 1080) |
|--|------------------------------------|---|
| Resolution | | |
| | 3840 x 2160; 6 frames/second | 1920 x 1080; 6 frames/second |
| | UHD 4K | HD |
| Viewing Range | | |
| | 70° Horizontal Field of View | 58.3° Horizontal Field of View |
| | 43° Vertical Field of View | 35.5° Vertical Field of View |
| | 360° Horizontal Pan | 360° Horizontal Pan |
| | -90° to 20° Vertical Tilt | 180° Vertical Tilt |
| | 12x Optical Zoom | 32x Optical Zoom |
| Dimensions | | |
| | 6.50" L (16.51 cm) | 7.38" L (18.75 cm) |
| | 6.50" W (16.51 cm) | 7.38" W (18.75 cm) |
| | 10.81" H (27.46 cm) | 8.56" H (21.74 cm) |
| Weight | | |
| | 6.5 lb (2.94 kg) | 5.5 lb (2.49 kg) |
| Operating Environment | | |
| | -40 °C to 50 °C (-40 °F to 122 °F) | -40 °C to 50 °C (-40 °F to 122 °F) |
| Data Connection | | Optional 110V AC Hardware |
| Wireless (Cellular LTE) | | Talk down speakers/strobe/microphone, battery backup, cabinet tamper-switch |
| Power Connection | | Optional Solar Security Hardware |
| 120/240 VAC (30 watts normal usage); Solar Compatible | | Talk down speaker/strobe/microphone and cabinet tamper-switch (backup battery already included) |
| Memory | | |
| Still Image - Unlimited Remote Storage Video - 128 GB onboard; approx 2 weeks | | |

Access to live video and video on demand requires login with a username. Monthly data usage limited to 30 GB per camera. Some live video products may provide up to two (2) weeks of local video archiving on the camera & data retrieval requires an additional fee. Three (3) year warranty on live video products from the date of purchase. Some exceptions may apply.

Every self-contained OxBlue construction camera comes ready to meet your jobsite monitoring needs right out of the box. No need for additional hardware or software - or jobsite internet connection.