

COBALT SERIES

TIME-LAPSE CAMERA



Every self-contained OxBlue construction camera comes ready to meet your jobsite monitoring needs right out of the box. No need for additional hardware or software - or jobsite internet connection.

COMPONENT	SPECIFICATION
Resolution	4 megapixel (2304 x 1728)
	6 megapixel (2816 x 2112)
	8 megapixel (3264 x 2448)
	12 megapixel (4000 x 3000)
	16 megapixel (4912 x 3264)
	24 megapixel (6000 x 4000)
	50 megapixel (8700 x 5800)
Memory	Unlimited Remote Storage
Data Connection	Wireless (Cellular LTE)
Power Connection	120 / 240 VAC (10 watts normal usage); Solar Compatible
Controller	Proprietary OxBlue System Embedded Industrial Computer
Dimensions	20.00" L (50.80 cm)
	8.50" W (21.59 cm)
	8.00" H (20.32 cm)
Optics	Up to 96° lens; Adjustable optical zoom
Weight	11.5 lb (5.22 kg) installed
Construction	Polycarbonate developed for the industry
Mounting	Wall, Pole, Ceiling, or Parapet Other mounts available at an additional cost
Operating Environment	-10 to 120° F
	-23 to 49° C
	90% non-condensing
	AC units - fan and defroster standard
	DC units - fan standard; emergency defroster